

# ESSENTIAL STUBBY SHOCK ABSORBER

PART NUMBER: **SHAB100** + Hardware

## DESCRIPTION

Shock Absorbing Assembly 380mm

## PRODUCT DETAILS

- Australian designed, engineered, and MADE.
- Rated for 140kg worker including tools and equipment.
- For use on a vertical travelling ladder system.
- First break out tear >200kg.
- Maximum breaking force/deceleration is less than 6kN.
- Ultimate load rating of 24kN once fully deployed.
- Drop forged lanyard hardware.
- Maximum freefall not to exceed 500mm. For free fall risks greater than 500mm use WLSA450 shock pack and connectors.

## STANDARDS

This product is manufactured using AS/NZS1891.1 compliant tear webbing, note that this stubby shock absorber cannot be used for freefalls greater than 500mm and for this reason the product cannot be marked as AS/NZS1891.1 certified.

### HARDWARE AVAILABLE

<b>KD</b>	Karabiner Double Action Steel Alloy 19mm
<b>KS</b>	Karabiner Screw Gate Steel Alloy 18mm
<b>KT</b>	Karabiner Triple Action Steel Alloy 26mm
<b>KTS</b>	Karabiner Triple Action Stainless Steel 27mm
<b>SD</b>	Scaffold Hook Double Action Steel Alloy 68mm
<b>ST</b>	Triple Action Scaffold Hook Steel Alloy 68mm
<b>GS</b>	Giant Double Action Scaffold Hook Aluminium 110mm
<b>SN</b>	Snap Hook

**Note:** 1st hardware code listed is connected to the body.  
e.g. KDSN Double action karabiner to body and snap hook on lanyard end.

**SHAB100KDSN** includes 1 x Karabiner Double Action & 1 x Snap Hook

**SHABKDSN** includes 1 x Karabiner Double Action & 2 x Snap Hook



**SHAB100**

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.  
If in doubt please contact the LINQ helpline.