

# **Australian Standard for Type 2 Speed Hump**

The Australian standard which regulates the design & use of speed hump for use in off-street parking in Australia is 'AS2890.1:2004 parking facilities'. AS2890.1 identifies four main criteria in the design of "type 2" speed humps.

- 1) Height:  
Must be between 25mm & 75mm.
- 2) Cross section:  
Must be flat on top. (Not round)
- 3) Ramp angle:  
Must have a ramp angle 2:1
- 4) Markings:  
Must have alternating parallel yellow or white stripes 250mm wide.


All our speed humps generally conform to the Australian Standards description of a type 2 hump & should be used as stated by standard as follows.

## **TYPE 2**


Appropriate for use in relatively confined areas or covered & multi storey car parks where it is desired to further check the speed of vehicles mostly travelling at 30km/h or less.

Road humps shall be spaced at no less than 10 metres for type 2, along any one aisle or roadway. Maximum spacing where required to control speeds continuously along a roadway should be about 50 metres, speed hump should be located clear of intersections & curved road ways.


Speed humps shall not impede pedestrian or wheelchair traffic on any accessible travel path provided for people with disabilities. **NOTE:** An accessible path of travel needs to be a minimum of 1 metre wide.




Height:



Cross Section:



Ramp Angle:



Markings:



## SLO-MOTION COMPLIANCE

Super Heavy Duty & Quiet

### Features:

- Designed and developed in Australia to comply with AS/NZS 2890.1:2004.
- Solid colour. U.V. stabilised, high tech composite plastic construction.
- Supplied with fixings ready for installation.
- Built-in prismatic reflectors for improved night visibility.
- Slip resistant texture moulded into surface.
- Built-in cable channel 27 x 30mm.
- Strengthened mounting points with large diameter load sharing washers.
- Low noise design suitable for residential areas.
- Light weight with incredible strength, able to take vehicles, trucks and buses etc.

<b>Material:</b>	Injection moulded Linear Low Density Polyethylene (LLDPE).
<b>Finish:</b>	Solid colour (Black or Yellow).
<b>Length:</b>	Body module – 250mm (i.e. 4 modules per metre). End cap – 180mm radius.
<b>Width:</b>	360mm (in the driving direction).
<b>Height:</b>	60mm.
<b>Ramp angle:</b>	2:1.
<b>Weight:</b>	Body module – 1.8kgs. End cap – 0.8kg.
<b>Fixings:</b>	2 per module (supplied).

PART No.	DESCRIPTION
SMC250Y	Slo-Motion compliance speed hump 250mm body module – Yellow
SMC250B	Slo-Motion compliance speed hump 250mm body module – Black
SMC250E	Slo-Motion compliance speed hump 180mm radius end caps – Black (pair)

Manufactured from  
environmentally friendly  
polyethylene (LLDPE)

